

HART Industrial O-Ring Unions are engineered to provide Class 3000 Service and are the most popular union in the industry for industrial applications. The flat face design provides turbulence-free fit across seats. This design is ideal where piping requirements dictate the necessity of having a flat face seal to make and break the pipe line. All HART Unions are made in the USA!

Standard O-Ring Union Features:


SURE SEAL O-RING UNIONS


- Turbulence Free: All unions provide a turbulence-free fit across the seats
- **O-Ring Isolation:** The O-Ring seal is strategically located in the thread piece face eliminating O-Ring media contact and added protection against abrasives and erosion. A variety of O-Rings for any application are available.
- **Precision Machined Components:** All unions are precision machined to provide high quality and fail-safe leak proof reliability.
- Interchangeable End Connections: Threaded (female and male), socket weld, and butt weld ends are interchangeable. This feature reduces overall costs by eliminating unnecessary nipples, bushings, couplings and inserts.
- Material Versatility: Unions can be provided in all standard metals or combination of metals. This includes 304 Stainless, 316 Stainless, A105 Carbon Steel, Brass, Monel 400, Hastalloy, and Titanium.
- Excellent Vibration Resistance: Seals will not loosen, even under extreme pressure and pressure surges.
- No Maintenance: Once initial seal is made, no further tightening required.

Union Dimensional Reference:

SIZE	A-Nominal	В	C-HEX	D	E-TAIL	F-THREAD	WEIGHT
D-3136-1	1/4″	1.63	1.50	0.86	0.78	0.83	0.33
D-3136-2	3/8″	1.82	1.69	1.02	0.88	0.91	0.4
D-3136-3	1/2″	1.94	1.87	1.23	0.92	0.99	0.7
D-3136-4	3/4″	2.36	2.20	1.46	1.11	1.23	1
D-3136-5	1″	2.45	2.62	1.79	1.17	1.25	1.75
D-3136-6	1-1/4″	2.80	3.06	2.16	1.38	1.39	2.5
D-3136-7	1-1/2″	3.01	3.37	2.42	1.50	1.17	3.5
D-3136-8	2″	3.40	4.14	2.96	1.65	1.72	4.25
D-3136-9	2-1/2″	4.03	5.00	3.61	1.98	2.01	6
D-3136-10	3″	4.30	5.62	4.30	2.13	2.13	8







NOTE: Dimensions are for reference only and are subject to change. "A-Nominal" refers to US nominal sizing. The tailpiece is nominal NPT and the threadpiece is nominal copper tube size (not outside diameter).

Questions? Call us at 1-800-769-0503. Our Customer Service and Engineering Teams are available to assist you with any needs!

HART Industrial Unions, LLC PO Box 310429 Newington, CT 06131 USA

Phone: 1-800-769-0503 Fax: 1-800-769-0504 www.hartindustries.com sales@hartindustries.com

